



## ACID AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x34	Porcelain	Non-Rectified	Matte	3/8"	11.33	4	Min. 1/8"

## ACID TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E≤0.5%
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 15045-14	Class 5



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Acid



# ACID

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

#### AVAILABLE COLORS

Acero  
Gris  
Oxido

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

#### RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

#### SHARE THIS LOOK



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	<a href="#">Beige &amp; Cream</a> , <a href="#">Brown</a> , <a href="#">Grey</a> , <a href="#">Red &amp; Orange</a>
<b>Material</b>	<a href="#">Stone</a>
<b>Finish</b>	<a href="#">Polished</a>
<b>Price</b>	<a href="#">\$\$</a>

Acid quantity

Add to cart

SKU: acid

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## ACID AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x34	Porcelain	Non-Rectified	Matte	3/8"	11.33	4	Min. 1/8"

## ACID TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E≤0.5%
Breaking Strength	ISO 10545-4	Compliant
MOH's Hardness	EN 0	MOHS 7

## Physical Properties

## Standard

## Results

Chemical Resistance

(Acid & Bases)

(Household Chemicals)

ISO 10545-13

GLA

GA

Stain Resistance

ISO 15045-14

Class 5

## RELATED PRODUCTS

- 

### PULPIS

\$0.00

- 

### CARBONITE

\$0.00

- 

### GLACIER

\$0.00