



SARK TILE

ACID AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 12x34 | Porcelain | Non-Rectified | Matte | 3/8" | 11.33 | 4 | Min. 1/8" |

ACID TILE PERFORMANCE DATA

| Physical Properties | Standard | Results |
|--|-----------------|-----------|
| Dynamic Coefficient of Friction | D.C.O.F. > 0.42 | ≥0.42 |
| Water Absorption | ISO 10545-3 | E≤0.5% |
| Breaking Strength | ISO 10545-4 | Compliant |
| MOH's Hardness | EN 0 | MOHS 7 |
| Chemical Resistance (Acid & Bases) (Household Chemicals) | ISO 10545-13 | GLA GA |
| Stain Resistance | ISO 15045-14 | Class 5 |



PRODUCT DESCRIPTION

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Acero
Gris
Oxido

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS LOOK

[GENERATE PDF](#)