



ALTAMIRA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
18x18	Porcelain	Non-Rectified	Matte	3/8"	15.75	7	Min. 1/8"
3x6 (Ivory & Walnut)	Porcelain	Rectified	Matte	3/8"	5.5	44	Min. 1/8"

ALTAMIRA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	<0.42
Water Absorption	ISO 10545-3	E≤0.5%
Breaking Strength	ISO 10545-4	Min 40
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLB GHB
Stain Resistance	ISO 15045-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Altamira



ALTAMIRA

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Ivory
Lava
Walnut

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Color	Beige & Cream , Brown
Material	Stone
Finish	Matte
Price	\$

Altamira quantity

Add to cart

SKU: altamira

Categories: [Glass & Accent Tile](#), [Porcelain & Ceramic Tile](#)

ALTAMIRA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
18x18	Porcelain	Non-Rectified	Matte	3/8"	15.75	7	Min. 1/8"
3x6 (Ivory & Walnut)	Porcelain	Rectified	Matte	3/8"	5.5	44	Min. 1/8"

ALTAMIRA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	<0.42
Water Absorption	ISO 10545-3	E≤0.5%
Breaking Strength	ISO 10545-4	Min 40
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLB GHB
Stain Resistance	ISO 15045-14	Class 5

RELATED PRODUCTS



CREFOR

\$0.00



BERSE

\$0.00



MANDALAY

\$0.00