



BEACHWOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Non-Rectified	Matte	3/8"	10.5	7	Min. 1/8"

BEACHWOOD TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	Min. 40
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	(Blanco) GLB, GHB (Burnished) GLA, GHA
Stain Resistance	ISO10545-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Beachwood







BEACHWOOD

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Blanco
Burnished

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior


[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream , Brown , White
Material	Wood
Finish	Matte
Price	\$

Beachwood quantity

[Add to cart](#)

SKU: beachwood

 Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

BEACHWOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Non-Rectified	Matte	3/8"	10.5	7	Min. 1/8"

BEACHWOOD TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	Min. 40
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	(Blanco) GLB, GHB (Burnished) GLA, GHA
Stain Resistance	ISO10545-14	Class 5

RELATED PRODUCTS



BRICK

\$0.00



CORK

\$0.00



ACID

\$0.00