BEACHWOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Non-Rectified	Matte	3/8"	10.5	7	Min. 1/8"

BEACHWOOD TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	Min. 40
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	(Blanco) GLB, GHB (Burnished) GLA, GHA
Stain Resistance	ISO10545-14	Class 5

PRODUCT DESCRIPTION

BEACHWOOD

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Blanco
Burnished

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown, White
Material	Wood
Finish	Matte
Price	$

Beachwood quantity
1

Add to cart

SKU: beachwood

Categories: Porcelain & Ceramic Tile, Trade Professionals

BEACHWOOD AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Non-Rectified	Matte	3/8"	10.5	7	Min. 1/8"

BEACHWOOD TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	Min. 40
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	(Blanco) GLB, GHB (Burnished) GLA, GHA
Stain Resistance	ISO10545-14	Class 5

RELATED PRODUCTS

- 

  ### CARBONITE

  $0.00

- 

  ### MONACO

  $0.00

- 

  ### CORK

  $0.00