



BERSE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	1/4"	14.25	7	Min. 1/8"
12x12	Porcelain	Mosaic 2x2	Matte	1/4"	6	6	

BERSE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	(Graphite) 5 (Grey) 4 (Nocce) 4
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Berse



BERSE

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Graphite
Grey
Nocce

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream , Grey , White
Material	Stone
Finish	Matte
Price	\$

Berse quantity

Add to cart

SKU: berse

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

BERSE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	1/4"	14.25	7	Min. 1/8"
12x12	Porcelain	Mosaic 2x2	Matte	1/4"	6	6	

BERSE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42

Physical Properties

	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	$> 1300 \text{ N}$
MOH's Hardness	EN 0	(Graphite) 5 (Grey) 4 (Nocce) 4
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	5

RELATED PRODUCTS

- 

SILK

\$0.00

- 

SARK STEEL

\$0.00

- 

MONACO

\$0.00