



BETON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	16	8	Min. 1/8"

BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Beton



BETON

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Fume
Grey
White

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Gray, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Material	Concrete
Finish	Matte
Price	\$

Beton quantity

Add to cart

SKU: beton

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

BETON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	16	8	Min. 1/8"

BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5

RELATED PRODUCTS



CORK

\$0.00



STONETREND

\$0.00



SILK

\$0.00