



## BETON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	16	8	Min. 1/8"

## BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5



# PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / [Concrete](#)





## BETON

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

### AVAILABLE COLORS

Beige  
Fume  
Grey  
White

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---

### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	Gray, White
<b>Material</b>	Wood, Stone, Concrete, Decorative, 3D Wall
<b>Material</b>	<a href="#">Concrete</a>

**Finish**

[Matte](#)

**Price**

\$

Beton quantity

Add to cart

SKU: beton

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## BETON AVAILABLE SIZES

Sizes	Type	Style	Finish Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte 3/8"	16	8	Min. 1/8"

## BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5

## RELATED PRODUCTS



### CEMENTI

\$0.00



## BEACHWOOD

\$0.00



## MANDALAY

\$0.00