BETON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	16	8	Min. 1/8"

BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5

PRODUCT DESCRIPTION

BETON

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Fume
Grey
White

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Gray, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Material	Concrete
Finish	Matte
Price	$

Beton quantity
1

Add to cart

SKU: beton

Categories: Porcelain & Ceramic Tile, Trade Professionals

BETON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	16	8	Min. 1/8"

BETON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
DSK Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.55
Water Absorption	ISO 10545-3	Max. 0.5
Breaking Strength	ISO 10545-4	Min. 40
Crazing Resistance by Autoclave	ISO 10545-11	Resistant at 5Atm. for 2 hours
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHA
Stain Resistance	ISO 15045-14	Class 5

RELATED PRODUCTS

- ## BRICK

  $0.00

- ## CREFOR

  $0.00

- ## SILK

  $0.00