



SARKOTILE

BETON AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Non-Rectified | Matte | 3/8" | 16 | 8 | Min. 1/8" |

BETON TILE PERFORMANCE DATA

| Physical Properties | Standard | Results |
|--|-----------------|--------------------------------|
| DSK Dynamic Coefficient of Friction | D.C.O.F. > 0.42 | ≥0.55 |
| Water Absorption | ISO 10545-3 | Max. 0.5 |
| Breaking Strength | ISO 10545-4 | Min. 40 |
| Crazing Resistance by Autoclave | ISO 10545-11 | Resistant at 5Atm. for 2 hours |
| Chemical Resistance (Acid & Bases) (Household Chemicals) | ISO 10545-13 | GLA GHA |
| Stain Resistance | ISO 15045-14 | Class 5 |



PRODUCT DESCRIPTION

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Fume
Grey
White

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE

[GENERATE PDF](#)