





SARKOTILE

BRIT STONE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	20.35	10	Min. 1/8"
13x13	Porcelain	Mosaic 2x2	Matte	3/8"	13.2	11	

BRIT STONE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min. 250
MOH's Hardness	EN 0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	4
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Shade and Texture Rating	CTDA "V"	V4
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass



PRODUCT DESCRIPTION

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Arena
Blanco
Graphite
Vision

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

[GENERATE PDF](#)