



SWERTE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x45	Porcelain	Rectified	Matte	3/8"	12.5	5	Min. 1/16"

CALCO TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm ²
MOH's Hardness	EN 0	MOHS 4
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA GHA
Stain Resistance	ISO 10545-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Calco



CALCO

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior


[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Material	Stone
Finish	Matte
Price	\$

Calco quantity

Add to cart

SKU: Calco

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

SWERTE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x45	Porcelain	Rectified	Matte	3/8"	12.5	5	Min. 1/16"

CALCO TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm2
MOH's Hardness	EN 0	MOHS 4
Chemical Resistance (Acid & Bases)		GLA
(Household Chemicals)	ISO 10545-13	GA
Stain Resistance	ISO 10545-14	GHA
		Class 5

RELATED PRODUCTS




BRICK

\$0.00



CEMENTI

\$0.00



CORCHO

\$0.00