



## SWERTE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x45	Porcelain	Rectified	Matte	3/8"	12.5	5	Min. 1/16"

## CALCO TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm2
MOH's Hardness	EN 0	MOHS 4
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA GHA
Stain Resistance	ISO 10545-14	Class 5



## PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / Calco



## CALCO

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---


[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	Brown, Gray, Black, White
<b>Material</b>	Wood, Stone, Concrete, Decorative, 3D Wall
<b>Material</b>	<a href="#">Stone</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	\$

Calco quantity

[Add to cart](#)

SKU: Calco

 Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## SWERTE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x45	Porcelain	Rectified	Matte	3/8"	12.5	5	Min. 1/16"

## CALCO TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm2
MOH's Hardness	EN   0	MOHS 4
Chemical Resistance (Acid & Bases)	ISO 10545-13	GLA GA
Stain Resistance (Household Chemicals)	ISO 10545-14	GHA Class 5

## RELATED PRODUCTS



## **BERSE**

\$0.00



## **TIMBER**

\$0.00



**ACID**

\$0.00