



CARBONITE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Relief	Matte	5/16"	12	6	Min. 1/8"

CARBONITE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Carbonite



CARBONITE

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Grey
Material	Stone
Finish	Matte
Price	\$

Carbonite quantity

Add to cart

SKU: carbonite

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

CARBONITE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Relief	Matte	5/16"	12	6	Min. 1/8"

CARBONITE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

RELATED PRODUCTS

-

MONACO

\$0.00



MANDALAY

\$0.00



BI'MAN

\$0.00