



## CASK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x48	Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"

## CASK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	>.42
Water Absorption	ISO 10545-3	<.5%
Breaking Strength	ISO 10545-4	>1300 N
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHA



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Cask



# CASK

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

## AVAILABLE FINISHES

Graphite  
Silver  
Tobacco

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

## RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

## SHARE THIS LOOK



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

Finish [Matte](#)  
Size [24x48](#)  
Style [Stone](#)

Cask quantity

Add to cart

SKU: Cask

Category: [Porcelain & Ceramic Tile](#)

## CASK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x48	Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"

## CASK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	>.42
Water Absorption	ISO 10545-3	<.5%
Breaking Strength	ISO 10545-4	>1300 N

## Physical Properties

## Standard

## Results

Chemical Resistance  
(Acid & Bases)  
(Household Chemicals)

ISO 10545-13

GHA

## RELATED PRODUCTS



### STEAMSHIP

\$0.00



### CEMENTI

\$0.00



### SARK STEEL

\$0.00