



CLINK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
16x48	Ceramic	Rectified	Lapatto	1/2"	16	3	1/8"

CLINK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	MIN 600 N 1441
Thermal Shock Resistance	ISO-10545-9	Fulfilled
Surface Hardness	UNE67101	4



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Clink



CLINK

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Dark 3D
Dark Flat
Snow 3D
Snow Flat

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall

SHARE THIS LOOK



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Finish [Lappato](#)
Size [16×48](#)
Style [Decorative](#)

Clink quantity

Add to cart

SKU: Clink

Category: [Porcelain & Ceramic Tile](#)

CLINK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
16x48	Ceramic	Rectified	Lapatto	1/2"	16	3	1/8"

CLINK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	MIN 600 N 1441
Thermal Shock Resistance	ISO-10545-9	Fulfilled
Surface Hardness	UNE67101	4

RELATED PRODUCTS



TIVOLI

\$0.00



BI'MAN

\$0.00



CEMENTONIA

\$0.00