



CORK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x24	Porcelain	Rectified	Matte	3/8"	16	4	Min. 1/16"
24x24 Deco	Porcelain	Rectified	Matte	3/8"	16	4	Min. 1/16"

CORK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	Max 0,5
Breaking Strength	ISO 10545-4	min. 40
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHB
Stain Resistance	ISO 10545-14	5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Cork



CORK

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Cork
Cork Deco

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Brown , Grey
Material	Concrete , Decorative
Finish	Matte
Price	\$

Cork quantity

Add to cart

SKU: cork

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

CORK AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x24	Porcelain	Rectified	Matte	3/8"	16	4	Min. 1/16"
24x24 Deco	Porcelain	Rectified	Matte	3/8"	16	4	Min. 1/16"

CORK TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	Max 0,5
Breaking Strength	ISO 10545-4	min. 40
MOH's Hardness	EN 0	

Physical Properties	Standard	Results
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHB
Stain Resistance	ISO 10545-14	5

RELATED PRODUCTS



MONACO

\$0.00



BI'MAN

\$0.00



BERSE

\$0.00