CREFOR AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x48	Porcelain	Rectified	Matte	3/8"	12	3	Min. 1/16"
12x24 Fumo Only	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

CREFOR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	> .60
Water Absorption	ISO 10545-3	E ≤ 0.5
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN|0|	8
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

PRODUCT DESCRIPTION

CREFOR

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Aria
Carbone
Fumo

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Brown, Grey, White
Material	Stone
Finish	Matte
Price	$$

Crefor quantity
1

Add to cart

SKU: crefor

Categories: Porcelain & Ceramic Tile, Trade Professionals

CREFOR AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x48	Porcelain	Rectified	Matte	3/8"	12	3	Min. 1/16"
12x24 Fumo Only	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

CREFOR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	> .60
Water Absorption	ISO 10545-3	E ≤ 0.5
Breaking Strength	ISO 10545-4	> 1300 N

Physical Properties	Standard	Results
MOH's Hardness	EN|0|	8
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

RELATED PRODUCTS

- ### CEMENTI

  $0.00

- ### TIVOLI

  $0.00

- ### MANDALAY

  $0.00