



## DEPOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/16"

## DEPOT TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	>35N/mm <sup>2</sup>
MOH's Hardness	EN 0	MOHS 5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	
Stain Resistance	ISO 10545-14	Meets or Exceeds



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Depot



# DEPOT

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

#### AVAILABLE COLORS

Graphite  
Grey  
Sand

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

#### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

#### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

**Color** Brown, Gray, Black, White  
**Material** Wood, Stone, Concrete, Decorative, 3D Wall

Depot quantity

Add to cart

SKU: depot

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## DEPOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/16"

## DEPOT TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	>35N/mm <sup>2</sup>
MOH's Hardness	EN   0	MOHS 5

## Physical Properties

## Standard

## Results

Chemical Resistance

(Acid & Bases)

ISO 10545-13

(Household Chemicals)

Stain Resistance

ISO 10545-14

Meets or Exceeds

## RELATED PRODUCTS



### GLACIER

\$0.00



### CREFOR

\$0.00



### TIMBER

\$0.00