



DEPOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/16"

DEPOT TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	>35N/mm ²
MOH's Hardness	EN 0	MOHS 5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	
Stain Resistance	ISO 10545-14	Meets or Exceeds



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Depot



DEPOT

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Graphite
Grey
Sand

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color Brown, Gray, Black, White
Material Wood, Stone, Concrete, Decorative, 3D Wall

Depot quantity

Add to cart

SKU: depot

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

DEPOT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/16"

DEPOT TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds
Water Absorption	ISO 10545-3	≤ 0.5%
Breaking Strength	ISO 10545-4	>35N/mm ²
MOH's Hardness	EN 0	MOHS 5

Physical Properties

Standard

Results

Chemical Resistance

(Acid & Bases)

(Household Chemicals)

ISO 10545-13

Stain Resistance

ISO 10545-14

Meets or Exceeds

RELATED PRODUCTS

- 

CEMENTI

\$0.00

- 

TIVOLI

\$0.00

- 

SARK STEEL

\$0.00