



SARKOTILE

ENCAUSTIC AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
7.5x7.5	Porcelain	Non-Rectified	Matte	5/16"	8.97	23	Min. 1/8"

ENCAUSTIC TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	Meets or Exceeds Standard
Breaking Strength	ISO 10545-4	Meets or Exceeds Standard
MOH's Hardness	EN 0	Meets or Exceeds Standard
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Meets or Exceeds Standard
Stain Resistance	ISO 10545-14	Meets or Exceeds Standard



PRODUCT DESCRIPTION

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

- Avenue
- Base Rock
- Base White
- Happy
- Leaves
- Poetry
- Round
- Sky
- Square

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

[GENERATE PDF](#)