



SARK  TILE

# EXCALIBUR AVAILABLE SIZES

---

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"
14x16 (Hexagon)	Porcelain	Non-Rectified	Matte	3/8"	10.2	9	Min/ 1/16"

# EXCALIBUR TILE PERFORMANCE DATA

---

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	>0.42
Water Absorption	ISO 10545-3	≤0.5%
Breaking Strength	ISO 10545-4	≥35 N /mm <sup>2</sup>
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Meets or Exceeds Standard
Stain Resistance	ISO 10545-14	Meets or Exceeds Standard



# PRODUCT DESCRIPTION

---

STOCKED IN LINCOLN, NE

## AVAILABLE COLORS

Grey

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

## RECOMMENDED INSTALLATIONS

Floor

Wall

Exterior

---

## SHARE THIS STYLE

[GENERATE PDF](#)