



EXCALIBUR AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"
14x16 (Hexagon)	Porcelain	Non-Rectified	Matte	3/8"	10.2	9	Min/ 1/16"

EXCALIBUR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	>0.42
Water Absorption	ISO 10545-3	≤0.5%
Breaking Strength	ISO 10545-4	≥35 N /mm ²
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Meets or Exceeds Standard
Stain Resistance	ISO 10545-14	Meets or Exceeds Standard



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Excalibur





EXCALIBUR

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Grey

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Color	Beige & Cream , Black , Brown , Grey
Material	Stone
Finish	Matte
Price	\$\$

Excalibur quantity

Add to cart

SKU: excalibur

Categories: [Limited Stock Title](#), [Porcelain & Ceramic Tile](#)

EXCALIBUR AVAILABLE SIZES

Sizes	Type	Style	Finish Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain Rectified	Matte	3/8"	12	6	Min. 1/16"
14x16 (Hexagon)	Porcelain Non-Rectified	Matte	3/8"	10.2	9	Min/ 1/16"

EXCALIBUR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	>0.42
Water Absorption	ISO 10545-3	≤0.5%
Breaking Strength	ISO 10545-4	≥35 N /mm ²
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Meets or Exceeds Standard
Stain Resistance	ISO 10545-14	Meets or Exceeds Standard

RELATED PRODUCTS



•

TIVOLI

\$0.00



•

CEMENTI

\$0.00



•

SARK STEEL

\$0.00