



## GEO AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
7x8 (Blanco, Carrara, Gris)	Porcelain	Hexagon	Matte	3/8"	11	35	Min. 5/64"
3.6x8.2 (Gris, Negro, Blanco)	Porcelain	Chevron	Matte	3/8"	11	54	Min. 5/64"
3.6x8.2 (Blanco)	Porcelain	Chevron	Glossy	3/8"	11	54	Min. 5/64"

## GEO HEXAGON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ISO 10545-3	< .05%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA
Stain Resistance	ISO 10545-14	5

## GEO CHEVRON MATTE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ISO 10545-3	< 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA
Stain Resistance	ISO 10545-14	5

## GEO CHEVRON GLOSSY TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	> 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN 0	3
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHB GA
Stain Resistance	ISO 10545-14	5



## PRODUCT DESCRIPTION



## GEO

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

### AVAILABLE COLORS

Blanco  
Carrara  
Gris  
Negro

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---

### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	Brown, Gray, Black, White
<b>Material</b>	Wood, Stone, Concrete, Decorative, 3D Wall
<b>Material</b>	<a href="#">Concrete</a> , <a href="#">Decorative</a>
<b>Finish</b>	<a href="#">Glossy</a> , <a href="#">Matte</a>
<b>Price</b>	<a href="#">\$\$\$</a>

Geo quantity

Add to cart

SKU: Geo

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## GEO AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
7x8 (Blanco, Carrara, Gris)	Porcelain	Hexagon	Matte	3/8"	11	35	Min. 5/64"
3.6x8.2 (Gris, Negro, Blanco)	Porcelain	Chevron	Matte	3/8"	11	54	Min. 5/64"
3.6x8.2 (Blanco)	Porcelain	Chevron	Glossy	3/8"	11	54	Min. 5/64"

## GEO HEXAGON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ISO 10545-3	< .05%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA
Stain Resistance	ISO 10545-14	5

## GEO CHEVRON MATTE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ISO 10545-3	< 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 0	7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA
Stain Resistance	ISO 10545-14	5

## GEO CHEVRON GLOSSY TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	> 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN 0	3
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GHB GA
Stain Resistance	ISO 10545-14	5

## RELATED PRODUCTS



### CEMENTONIA

\$0.00



**BRICK**

\$0.00



**TIVOLI**

\$0.00