MADISON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x63	Porcelain	Rectified	Matte	3/8"	14	4	Min. 1/16"

MADISON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm2
MOH's Hardness	EN|0|	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA GHA
Stain Resistance	ISO 10545-14	Class 4

PRODUCT DESCRIPTION

MADISON

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Ash
Maple

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Material	Wood
Finish	Matte
Price	$$

Madison quantity
1

Add to cart

SKU: Madison

Categories: Porcelain & Ceramic Tile, Trade Professionals

MADISON AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x63	Porcelain	Rectified	Matte	3/8"	14	4	Min. 1/16"

MADISON TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	
Water Absorption	ISO 10545-3	<0,5%
Breaking Strength	ISO 10545-4	>35N/mm2
MOH's Hardness	EN|0|	MOHS 7

Physical Properties	Standard	Results
Chemical Resistance		GLA
(Acid & Bases)	ISO 10545-13	GA
(Household Chemicals)		GHA
Stain Resistance	ISO 10545-14	Class 4

RELATED PRODUCTS

- ### CARBONITE

  $0.00

- ### STONETREND

  $0.00

- ### CORCHO

  $0.00