



## MARMORE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	20.35	10	Min. 1/8"
13x13	Porcelain	Mosaic 2x2	Matte	3/8"	13.2	11	

## MARMORE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min. 300
MOH's Hardness	EN 0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	4
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	$\geq 0.42$
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass




# PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / Marmore





## MARMORE

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

### AVAILABLE COLORS

Arena  
Blanco  
Graphite  
Gris

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---

### SHARE THIS STYLE



## ADDITIONAL INFORMATION

<b>Color</b>	Gray, White, Beige
<b>Material</b>	Stone
<b>Material</b>	<a href="#">Stone</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	\$

Marmore quantity

Add to cart

SKU: Marmore

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## MARMORE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	20.35	10	Min. 1/8"
13x13	Porcelain	Mosaic 2x2	Matte	3/8"	13.2	11	

## MARMORE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min. 300
MOH's Hardness	EN  0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	4
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	$\geq 0.42$
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass

## RELATED PRODUCTS



## MONACO

\$0.00



## CEMENTONIA

\$0.00



**ACID**

\$0.00