



SARKOTILE

MIKKIS AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 16x24 | Porcelain | Non-Rectified | Matte | 3/8" | 13.35 | 5 | Min. 1/8" |

MIKKIS TILE PERFORMANCE DATA

| Physical Properties | Standard | Results |
|--|-----------------|---------------------------|
| Dynamic Coefficient of Friction | D.C.O.F. > 0.42 | Meets or Exceeds Standard |
| Water Absorption | ISO 10545-3 | Meets or Exceeds Standard |
| Breaking Strength | ISO 10545-4 | Meets or Exceeds Standard |
| MOH's Hardness | EN 0 | Meets or Exceeds Standard |
| Chemical Resistance (Acid & Bases) (Household Chemicals) | ISO 10545-13 | Meets or Exceeds Standard |
| Stain Resistance | ISO 10545-14 | Meets or Exceeds Standard |



PRODUCT DESCRIPTION

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

[GENERATE PDF](#)