MODERN SLATE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	5/16"	13.56	7	
3x24 Bullnose	Porcelain	Rectified	Matte	5/16"		10	
12x12	Porcelain	Mosaic 2x2	Matte	5/16"	9.69	10	
6x12 Covebase	Porcelain	Rectified	Matte	5/16"		20	
10x12 (Multi-colored)	Porcelain	Mosaic Hex	Matte	5/16"	8.07	10	
12x24 Off-set Stripes	Porcelain	Mosaic	Matte	5/16"	3.88	2	

MODERN SLATE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

PRODUCT DESCRIPTION

MODERN SLATE

$0.00

- Description
- Additional information

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Anthracite
Lead
Sand
Silver
Volcano

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Black, Grey, Silver
Material	Stone
Finish	Matte
Price	$

Modern Slate quantity
1

Add to cart

SKU: modern-slate

Categories: Porcelain & Ceramic Tile, Trade Professionals

MODERN SLATE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	5/16"	13.56	7	
3x24 Bullnose	Porcelain	Rectified	Matte	5/16"		10	
12x12	Porcelain	Mosaic 2x2	Matte	5/16"	9.69	10	
6x12 Covebase	Porcelain	Rectified	Matte	5/16"		20	
10x12 (Multi-colored)	Porcelain	Mosaic Hex	Matte	5/16"	8.07	10	
12x24 Off-set Stripes	Porcelain	Mosaic	Matte	5/16"	3.88	2	

MODERN SLATE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

RELATED PRODUCTS

- ### GLACIER

  $0.00

- ### SILK

  $0.00

- ### CREFOR

  $0.00