



MODERN SLATE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	5/16"	13.56	7	
3x24 Bullnose	Porcelain	Rectified	Matte	5/16"		10	
12x12	Porcelain	Mosaic 2x2	Matte	5/16"	9.69	10	
6x12 Covebase	Porcelain	Rectified	Matte	5/16"		20	
10x12 (Multi-colored)	Porcelain	Mosaic Hex	Matte	5/16"	8.07	10	
12x24 Off-set Stripes	Porcelain	Mosaic	Matte	5/16"	3.88	2	

MODERN SLATE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Modern Slate





MODERN SLATE

\$0.00

- [Description](#)
- [Additional information](#)

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Anthracite
Lead
Sand
Silver
Volcano

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Black , Grey , Silver
Material	Stone
Finish	Matte
Price	\$

Modern Slate quantity

Add to cart

SKU: modern-slate

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

MODERN SLATE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
-------	------	-------	--------	-----------	-------------	------------	-------------------------

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain Non-Rectified	Matte	5/16"	13.56	7		
3x24 Bullnose	Porcelain Rectified	Matte	5/16"		10		
12x12	Porcelain Mosaic 2x2	Matte	5/16"	9.69	10		
6x12 Covebase	Porcelain Rectified	Matte	5/16"		20		
10x12 (Multi-colored)	Porcelain Mosaic Hex	Matte	5/16"	8.07	10		
12x24 Off-set Stripes	Porcelain Mosaic	Matte	5/16"	3.88	2		

MODERN SLATE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

RELATED PRODUCTS



SARK STEEL

\$0.00



CEMENTI

\$0.00



CREFOR

\$0.00