



## NATURE AVAILABLE SIZES

| Sizes         | Type      | Style         | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|---------------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 8x40          | Porcelain | Non-Rectified | Matte  |           | 12.92       | 6          |                         |
| 6x12 Covebase | Porcelain | Rectified     | Matte  |           | 9.69        | 20         |                         |

## NATURE TILE PERFORMANCE DATA

| Physical Properties                          | Test ASTM     | North American Standard A137.1 | Results                 |
|--|---------------|--------------------------------|-------------------------|
| Water Absorption                             | C373          | ≤0.5%                          | Comply with ANSI A137.1 |
| DCOF Average Dynamic Coefficient of Friction | BOT 3000 test | ≥0.42                          | ≥0.42                   |
| Resistance to freeze/thaw cycling            | C1026         | As reported                    | Resistant               |
| Warpage (edge)                               | C485          | Warpage ± 0.4% or ± 0.05 in    | Comply with ANSI A137.1 |
| Warpage (diagonal)                           | C485          | Warpage ± 0.4% or ± 0.07 in    | Comply with ANSI A137.1 |
| Wedging                                      | C502          | ± 0.25% or ± 0.03 in           | Comply with ANSI A137.1 |
| Chemical Resistance                          | C650          | As reported                    | Unaffected              |
| Breaking Strength                            | C648          | 250 lbf or greater             | Comply with ANSI A137.1 |
| Thickness                                    | C499          | Range: 0.04 in                 | Comply with ANSI A137.1 |



## PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / Nature


















# NATURE

\$0.00

- [Description](#)
- [Additional information](#)

1-2 WEEK LEAD TIME

## AVAILABLE COLORS

- Walnut
- Wedge
- Oak
- Maple
- Chestnut

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

|          |   |
|----------|---|
| Color    | <a href="#">Beige &amp; Cream</a> , <a href="#">Brown</a> |
| Material | <a href="#">Wood</a>                                      |
| Finish   | <a href="#">Matte</a>                                     |
| Price    | <a href="#">\$\$\$</a>                                    |

Nature quantity

Add to cart

SKU: nature

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

NATURE AVAILABLE SIZES

| Sizes         | Type      | Style         | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|---------------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 8x40          | Porcelain | Non-Rectified | Matte  |           | 12.92       | 6          |                         |
| 6x12 Covebase | Porcelain | Rectified     | Matte  |           | 9.69        | 20         |                         |

NATURE TILE PERFORMANCE DATA

| Physical Properties                          | Test ASTM     | North American Standard A137.1 | Results                 |
|--|---------------|--------------------------------|-------------------------|
| Water Absorption                             | C373          | ≤0.5%                          | Comply with ANSI A137.1 |
| DCOF Average Dynamic Coefficient of Friction | BOT 3000 test | ≥0.42                          | ≥0.42                   |
| Resistance to freeze/thaw cycling            | C1026         | As reported                    | Resistant               |
| Warpage (edge)                               | C485          | Warpage ± 0.4% or ± 0.05 in    | Comply with ANSI A137.1 |
| Warpage (diagonal)                           | C485          | Warpage ± 0.4% or ± 0.07 in    | Comply with ANSI A137.1 |
| Wedging                                      | C502          | ± 0.25% or ± 0.03 in           | Comply with ANSI A137.1 |
| Chemical Resistance                          | C650          | As reported                    | Unaffected              |
| Breaking Strength                            | C648          | 250 lbf or greater             | Comply with ANSI A137.1 |
| Thickness                                    | C499          | Range: 0.04 in                 | Comply with ANSI A137.1 |



RELATED PRODUCTS



STONETREND

\$0.00



CREFOR

\$0.00



**BI'MAN**

\$0.00