

NATURE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte		12.92	6	
6x12 Covebase	Porcelain	Rectified	Matte		9.69	20	

NATURE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	$\leq 0.5\%$	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥ 0.42	≥ 0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage $\pm 0.4\%$ or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage $\pm 0.4\%$ or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	$\pm 0.25\%$ or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Nature



\$0.00

- [Description](#)
- [Additional information](#)

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Walnut
Wedge
Oak
Maple
Chestnut

Please contact the office for availability. [402-475-1300](#)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown
Material	Wood
Finish	Matte
Price	\$\$\$

Nature quantity

Add to cart

SKU: nature

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

NATURE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended	Grout	Joint
8x40	Porcelain	Non-Rectified	Matte		12.92	6			
6x12 Covebase	Porcelain	Rectified	Matte		9.69	20			

NATURE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	$\leq 0.5\%$	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥ 0.42	≥ 0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage $\pm 0.4\%$ or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage $\pm 0.4\%$ or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	$\pm 0.25\%$ or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

RELATED PRODUCTS



CEMENTONIA

\$0.00



ACID

\$0.00



TIVOLI

\$0.00