NATURE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte		12.92	6	
6x12 Covebase	Porcelain	Rectified	Matte		9.69	20	

NATURE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

PRODUCT DESCRIPTION

NATURE

$0.00

- Description
- Additional information

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Walnut
Wedge
Oak
Maple
Chestnut

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Beige & Cream, Brown
Material	Wood
Finish	Matte
Price	$$$

Nature quantity
1

Add to cart

SKU: nature

Categories: Porcelain & Ceramic Tile, Trade Professionals

NATURE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte		12.92	6	
6x12 Covebase	Porcelain	Rectified	Matte		9.69	20	

NATURE TILE PERFORMANCE DATA

Physical Properties	Test ASTM	North American Standard A137.1	Results
Water Absorption	C373	≤0.5%	Comply with ANSI A137.1
DCOF Average Dynamic Coefficient of Friction	BOT 3000 test	≥0.42	≥0.42
Resistance to freeze/thaw cycling	C1026	As reported	Resistant
Warpage (edge)	C485	Warpage ± 0.4% or ± 0.05 in	Comply with ANSI A137.1
Warpage (diagonal)	C485	Warpage ± 0.4% or ± 0.07 in	Comply with ANSI A137.1
Wedging	C502	± 0.25% or ± 0.03 in	Comply with ANSI A137.1
Chemical Resistance	C650	As reported	Unaffected
Breaking Strength	C648	250 lbf or greater	Comply with ANSI A137.1
Thickness	C499	Range: 0.04 in	Comply with ANSI A137.1

RELATED PRODUCTS

- ## PULPIS

  $0.00

- ## BEACHWOOD

  $0.00

- ## METRO

  $0.00