



SARKOTILE

NEO AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|--------------------------|-----------|-----------|--------|-----------|-------------|------------|-------------------------|
| 8x48 | Porcelain | Rectified | Matte | 3/8" | 10.08 | 4 | |
| 3.5x17.3 (Fresno & Gris) | Porcelain | Chevron | Matte | 3/8" | 5.66 | 10 | |

NEO TILE PERFORMANCE DATA

| Physical Properties | ASTM Test | ISO Test | Value Required ANSI | Declared ASTM |
|--|-------------|--------------|----------------------|---------------|
| Water Absorption | C373 | ISO-10545/3 | <=0.5% | <=0.5% |
| Break Strength | C648 | ISO-10545/4 | >=250 | Min. 450 |
| Scratch Hardness | MOH's Scale | EN-101 | - | 7 |
| Chemical Resistance | C650 | ISO-10545/13 | Unaffected | Unaffected |
| Frost Resistance | C1026 | ISO-10545/12 | Resistant | Resistant |
| Group | SEE FAQs | SEE FAQs | - | 4 |
| Deep Abrasion - Unglazed Tiles | C1234 | ISO-10545/6 | <175 mm ³ | Pass |
| PEI - Glazed Tiles | C1027 | ISO-10545/7 | - | - |
| Minimum Bond Strength (PSI) | C482 | | >=50 psi | 165 |
| Dynamic Coefficient of Friction (DCOF) | A137.1 | - | >=0.42 | 0.42 |
| Shade and Texture Rating | CTDA "V" | - | - | V3 |
| Facial Dimensions | C499 | ISO-10545/2 | 1.5% Max | Pass |
| Range of Thickness | C499 | ISO-10545/2 | 0.040 Max | Pass |
| Warpage | C485 | ISO-10545/2 | 0.75% | Pass |
| Wedging | C502 | ISO-10545/2 | 1.0% Max | Pass |

NEO CHEVRON TILE PERFORMANCE DATA

| Physical Properties | ASTM Test | ISO Test | Value Required ANSI | Declared ASTM |
|--|-------------|--------------|---------------------|---------------|
| Water Absorption | C373 | ISO-10545/3 | <=0.5% | <=0.5% |
| Break Strength | C648 | ISO-10545/4 | >=250 | Min. 290 |
| Scratch Hardness | MOH's Scale | EN-101 | - | 5 |
| Chemical Resistance | C650 | ISO-10545/13 | Unaffected | Unaffected |
| Frost Resistance | C1026 | ISO-10545/12 | Resistant | Resistant |
| Group | SEE FAQs | SEE FAQs | - | 4 |
| Deep Abrasion - Unglazed Tiles | C1234 | ISO-10545/6 | <175 mm3 | - |
| PEI - Glazed Tiles | C1027 | ISO-10545/7 | - | 5 |
| Minimum Bond Strength (PSI) | C482 | | >=50 psi | 165 |
| Dynamic Coefficient of Friction (DCOF) | A137.1 | - | >=0.42 | <=0.45 |
| Shade and Texture Rating | CTDA "V" | - | - | V3 |
| Facial Dimensions | C499 | ISO-10545/2 | 1.5% Max | Pass |
| Range of Thickness | C499 | ISO-10545/2 | 0.040 Max | Pass |
| Warpage | C485 | ISO-10545/2 | 0.75% | Pass |
| Wedging | C502 | ISO-10545/2 | 1.0% Max | Pass |



PRODUCT DESCRIPTION

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Fresno
Gris
Sapeli
Taupe

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

[GENERATE PDF](#)