NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3

PRODUCT DESCRIPTION

NOVA

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Emperador
Lasa
Oxford
Statuario

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



GENERATE PDF

ADDITIONAL INFORMATION

Color	Gray, White, Black
Material	Stone
Material	Stone
Finish	Matte
Price	$$

Nova quantity
1

Add to cart

SKU: Nova

Categories: Porcelain & Ceramic Tile, Trade Professionals

NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3

RELATED PRODUCTS

- ## CARBONITE

  $0.00

- ## CORK

  $0.00

- ## BERSE

  $0.00