



## NOVA AVAILABLE SIZES

| Sizes | Type      | Style     | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|-----------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Rectified | Matte  | 3/8"      | 12          | 6          | Min. 1/16"              |

## NOVA TILE PERFORMANCE DATA

| Physical Properties  | Standard        | Results  |
|--|-----------------|----------|
| Dynamic Coefficient of Friction                                | D.C.O.F. > 0.42 | ≥0.42    |
| Water Absorption   | ISO 10545-3     | E ≤ 0.5% |
| Breaking Strength  | ISO 10545-4     | > 1300 N |
| MOH's Hardness   | EN 101          | >5       |
| Chemical Resistance<br>(Acid & Bases)<br>(Household Chemicals) | ISO 10545-13    | Class B  |
| Stain Resistance   | ISO 10545-14    | 3        |



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Nova



# NOVA

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

## AVAILABLE COLORS

Emperador  
Lasa  
Oxford  
Statuario

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

## RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

---

## SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

|                 |                       |
|-----------------|-----------------------|
| <b>Color</b>    | Gray, White, Black    |
| <b>Material</b> | Stone                 |
| <b>Material</b> | <a href="#">Stone</a> |
| <b>Finish</b>   | <a href="#">Matte</a> |
| <b>Price</b>    | <a href="#">\$\$</a>  |

Nova quantity

Add to cart

SKU: Nova

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## NOVA AVAILABLE SIZES

| Sizes | Type      | Style     | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|-------|-----------|-----------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Rectified | Matte  | 3/8"      | 12          | 6          | Min. 1/16"              |

# NOVA TILE PERFORMANCE DATA

| Physical Properties  | Standard        | Results        |
|--|-----------------|----------------|
| Dynamic Coefficient of Friction                                | D.C.O.F. > 0.42 | $\geq 0.42$    |
| Water Absorption   | ISO 10545-3     | $E \leq 0.5\%$ |
| Breaking Strength  | ISO 10545-4     | > 1300 N       |
| MOH's Hardness   | EN 101          | >5             |
| Chemical Resistance<br>(Acid & Bases)<br>(Household Chemicals) | ISO 10545-13    | Class B        |
| Stain Resistance   | ISO 10545-14    | 3              |

## RELATED PRODUCTS



### CARBONITE

\$0.00



### CREFOR

\$0.00



### CORCHO

\$0.00