



NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Nova





NOVA

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Emperador
Lasa
Oxford
Statuario

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Gray, White, Black
Material	Stone
Material	Stone

Finish
Price

[Matte](#)
[\\$\\$](#)

Nova quantity

Add to cart

SKU: Nova

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3

RELATED PRODUCTS



ACID

\$0.00



•
PULPIS

\$0.00



•
CORK

\$0.00