



## NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

## NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥0.42
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Nova



# NOVA

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

## AVAILABLE COLORS

Emperador  
Lasa  
Oxford  
Statuario

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

## RECOMMENDED INSTALLATIONS

Wall  
Floor  
Exterior

## SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	Gray, White, Black
<b>Material</b>	Stone
<b>Material</b>	<a href="#">Stone</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	<a href="#">\$\$</a>

Nova quantity

Add to cart

SKU: Nova

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## NOVA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Rectified	Matte	3/8"	12	6	Min. 1/16"

# NOVA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	$\geq 0.42$
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	> 1300 N
MOH's Hardness	EN 101	>5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Class B
Stain Resistance	ISO 10545-14	3

## RELATED PRODUCTS



### STONETREND

\$0.00



### CEMENTONIA

\$0.00



### TIVOLI

\$0.00