



PEDRA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	20.35	10	Min. 1/8"
13x13	Porcelain	Mosaic 2x2	Matte	3/8"	13.2	11	


PEDRA TILE PERFORMANCE DATA


Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min. 300
MOH's Hardness	EN 0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	4-2 (BL)
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warpage	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Pedra





PEDRA

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Black
Gris
Pewter
Soft Gris

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Gray, White, Beige
Material	Stone
Material	Stone
Finish	Matte
Price	\$

Pedra quantity

Add to cart

SKU: Pedra

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

PEDRA AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	20.35	10	Min. 1/8"
13x13	Porcelain	Mosaic 2x2	Matte	3/8"	13.2	11	

PEDRA TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min. 300
MOH's Hardness	EN 0	5
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Unaffected
Frost Resistance	ISO 10545-12	Resistant
PEI-Glazed Tiles	ISO 10545-7	4-2 (BL)
Minimum Bond Strength (PSI)	C482	165
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Shade and Texture Rating	CTDA "V"	V3
Facial Dimensions	ISO 10545-2	Pass
Range of Thickness	ISO 10545-2	Pass
Warping	ISO 10545-2	Pass
Wedging	ISO 10545-2	Pass

RELATED PRODUCTS



CORCHO

\$0.00



TIMBER

\$0.00



• **SARK STEEL**

\$0.00