



PORT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x48	Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"
24x48 3D	Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"

COPY OF OKUR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Slip Resistance	DCOF	>0.42
Water Absorption	ISO 10545-3	≤.5%
Breaking Strength	ISO 10545-4	>1300 N
Variation		V2
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Gla GHA
Stain Resistance	ISO 10545-14	Class 5
Scratch Hardness	ISOEN 10545-7	PEI IV

PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Port

PORT





\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

COLORS AVAILABLE

Beige
Beige 3D
Ivory
Ivory 3D
Taupe
Taupe 3D
White
White 3D

SIZES AVAILABLE

24x48

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Interior | Exterior | Wall | Wet

SHARE THIS LOOK



ADDITIONAL INFORMATION

Color	Beige & Cream , Brown , White
Finish	Matte
Size	24x48
Style	Stone

Port quantity

Add to cart

SKU: Port 24x48

Categories: [Ceramic Tile](#), [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

PORT AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x48	Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"
24x48	3D Porcelain	Rectified	Matte	3/8"	15.75	2	1/8"

COPY OF OKUR TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Slip Resistance	DCOF	>0.42
Water Absorption	ISO 10545-3	≤.5%
Breaking Strength	ISO 10545-4	>1300 N
Variation		V2
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Gla GHA
Stain Resistance	ISO 10545-14	Class 5
Scratch Hardness	ISOEN 10545-7	PEI IV

YOU MAY ALSO LIKE...



VENA

\$0.00



OGNA

\$0.00



CALIZA

\$0.00

RELATED PRODUCTS



BEACHWOOD

\$0.00



BERSE

\$0.00



SARK STEEL

\$0.00