



## PULPIS AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
32x48	Porcelain	Rectified	Glossy	1/2"	21.34	2	Min. 1/8"

## PULPIS TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	COF > 0.4
Water Absorption	ISO 10545-3	≤ 0.05%
Breaking Strength	ISO 10545-4	46 N/mm <sup>2</sup>
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	No Damage
Stain Resistance	ISO 10545-14	Resistance



## PRODUCT DESCRIPTION

---

[Home](#) / [Porcelain & Ceramic Tile](#) / Pulpis



## PULPIS

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

---

### RECOMMENDED INSTALLATIONS

Wall  
Floor

---

SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

Color	<a href="#">Grey</a>
Material	<a href="#">Stone</a>
Finish	<a href="#">Glossy</a>
Price	<a href="#">\$\$\$</a>

Pulpis quantity

Add to cart

SKU: pulpis

Category: [Porcelain & Ceramic Tile](#)

## PULPIS AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
32x48	Porcelain	Rectified	Glossy	1/2"	21.34	2	Min. 1/8"

## PULPIS TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	COF > 0.4
Water Absorption	ISO 10545-3	≤ 0.05%
Breaking Strength	ISO 10545-4	46 N/mm <sup>2</sup>
MOH's Hardness	EN   0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	No Damage
Stain Resistance	ISO 10545-14	Resistance

## RELATED PRODUCTS



## BI'MAN

\$0.00



## GLACIER

\$0.00



## CORK

\$0.00