



PULPIS AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
32x48	Porcelain	Rectified	Glossy	1/2"	21.34	2	Min. 1/8"

PULPIS TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	COF > 0.4
Water Absorption	ISO 10545-3	≤ 0.05%
Breaking Strength	ISO 10545-4	46 N/mm ²
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	No Damage
Stain Resistance	ISO 10545-14	Resistance



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Pulpis



PULPIS

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Grey
Material	Stone
Finish	Glossy
Price	\$\$\$

Pulpis quantity

Add to cart

SKU: pulpis

Category: [Porcelain & Ceramic Tile](#)

PULPIS AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
32x48	Porcelain	Rectified	Glossy	1/2"	21.34	2	Min. 1/8"

PULPIS TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	COF > 0.4
Water Absorption	ISO 10545-3	≤ 0.05%
Breaking Strength	ISO 10545-4	46 N/mm ²
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	No Damage
Stain Resistance	ISO 10545-14	Resistance

RELATED PRODUCTS



CEMENTI

\$0.00



BERSE

\$0.00



CARBONITE

\$0.00