



SARK STEEL AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x24	Porcelain	Rectified		7/16"	12	3	Min. 1/16"
12x24 (Black, Rust)	Porcelain	Rectified		7/16"	12	6	
3x12 Bullnose (Black, Rust)	Porcelain			7/16"		15	
12x12 (Black, Rust)	Porcelain	Mosaic 1x3 Stacked		7/16"	10	10	
13x13 (Rust)	Porcelain	Mosaic Curve		7/16"	10.62	9	
2.5x24 Listelo (Rust)	Porcelain			7/16"		14	

SARK STEEL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.08\%$
Breaking Strength	ISO 10545-4	Resists
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Resists
Stain Resistance	ISO 10545-14	Resists



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Sark Steel



SARK STEEL

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Black
Rust

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream , Black , Grey , Multicolor , Red & Orange
Material	Stone
Finish	Lappato
Price	\$\$

Sark Steel quantity

Add to cart

SKU: sark-steel

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

SARK STEEL AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
24x24	Porcelain	Rectified		7/16"	12	3	Min. 1/16"
12x24 (Black, Rust)	Porcelain	Rectified		7/16"	12	6	
3x12 Bullnose (Black, Rust)	Porcelain			7/16"		15	
12x12 (Black, Rust)	Porcelain	Mosaic 1x3 Stacked		7/16"	10	10	

Sizes	Type	Style	Finish Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
13x13 (Rust)	Porcelain Mosaic Curve		7/16"	10.62	9	
2.5x24 Listelo (Rust)	Porcelain		7/16"		14	

SARK STEEL TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.08\%$
Breaking Strength	ISO 10545-4	Resists
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	Resists
Stain Resistance	ISO 10545-14	Resists

RELATED PRODUCTS



CEMENTI

\$0.00



TIVOLI

\$0.00



MONACO

\$0.00