



STONETREND AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x24	Porcelain	Rectified	Matte	3/8"	10	10	Min. 1/16"
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/8"
12x12	Porcelain	Mosaic 2x2	Matte	3/8"	8	8	

STONETREND TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.5\%$
Breaking Strength	ISO 10545-4	Min 40
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Stonetrend



STONETREND

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Anthracite
Cream
Grey

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream , Grey
Material	Stone
Finish	Matte
Price	\$

Stonetrend quantity

Add to cart

SKU: stonetrend

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

STONETREND AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x24	Porcelain	Rectified	Matte	3/8"	10	10	Min. 1/16"
12x24	Porcelain	Rectified	Matte	3/8"	16	8	Min. 1/8"
12x12	Porcelain	Mosaic 2x2	Matte	3/8"	8	8	

STONETREND TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E ≤ 0.5%
Breaking Strength	ISO 10545-4	Min 40
MOH's Hardness	EN 0	MOHS 7
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Class 5

RELATED PRODUCTS



TIVOLI

\$0.00



SILK

\$0.00



BI'MAN

\$0.00