



TENNESSEE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte	3/8"	15.07	7	

TENNESSEE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Tennessee



TENNESSEE

\$0.00

- [Description](#)
- [Additional information](#)

1-2 WEEK LEAD TIME

AVAILABLE COLORS

Chestnut
Grey

RECOMMENDED INSTALLATIONS

Wall
Floor
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Brown, Gray, Black, White
Material	Wood, Stone, Concrete, Decorative, 3D Wall
Color	Brown , Grey
Finish	Matte
Material	Wood
Price	\$

Tennessee quantity

Add to cart

SKU: tennessee

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

TENNESSEE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
8x40	Porcelain	Non-Rectified	Matte	3/8"	15.07	7	

TENNESSEE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	≥ 0.42
Water Absorption	ANSI A137.1	≤ 0.5%
Resistance to freeze/thaw cycling	ASTM C1026	Resistant
Warpage (diagonal)	Warpage ± 0.4% or ± 0.07 in.	Comply with ANSI A137.1
Warpage (edge)	Warpage ± 0.4% or ± 0.05 in.	Comply with ANSI A137.1
Chemical Resistance (Acid & Bases) (Household Chemicals)	ASTM C650	Unaffected
Thickness	ASTM C499	Comply with ANSI A137.1
Wedging	± 0.25% or ± 0.03 in	Comply with ANSI A137.1

RELATED PRODUCTS



SARK STEEL

\$0.00



BI'MAN

\$0.00



PULPIS

\$0.00