TIMBER AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Rectified	Matte	7/16"	12	8	Min. 1/8"

TIMBER TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	D.C.O.F. ≥ 0.42
Water Absorption	ISO 10545-3	E ≤ 0.09%
Breaking Strength	ISO 10545-4	Complaint
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

PRODUCT DESCRIPTION

TIMBER

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Dorado
Noche
Oyster
Salvia

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Brown
Material	Wood
Finish	Matte
Price	$

Timber quantity
1

Add to cart

SKU: timber

Categories: Porcelain & Ceramic Tile, Trade Professionals

TIMBER AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Rectified	Matte	7/16"	12	8	Min. 1/8"

TIMBER TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	D.C.O.F. ≥ 0.42

Physical Properties	Standard	Results
Water Absorption	ISO 10545-3	E ≤ 0.09%
Breaking Strength	ISO 10545-4	Complaint
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

RELATED PRODUCTS

-

  ### CORCHO

  $0.00

-

  ### SARK STEEL

  $0.00

-

  ### COLORADO

  $0.00