



## TIMBER AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Rectified	Matte	7/16"	12	8	Min. 1/8"

## TIMBER TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	D.C.O.F. ≥ 0.42
Water Absorption	ISO 10545-3	E ≤ 0.09%
Breaking Strength	ISO 10545-4	Complaint
MOH's Hardness	EN   0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5



## PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Timber



# TIMBER

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

## AVAILABLE COLORS

Dorado  
Noche  
Oyster  
Salvia

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

## RECOMMENDED INSTALLATIONS

Floor  
Wall  
Exterior

## SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

Color	<a href="#">Brown</a>
Material	<a href="#">Wood</a>
Finish	<a href="#">Matte</a>
Price	<a href="#">\$</a>

Timber quantity

Add to cart

SKU: timber

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

## TIMBER AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
6x36	Porcelain	Rectified	Matte	7/16"	12	8	Min. 1/8"

## TIMBER TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	D.C.O.F. ≥ 0.42

## Physical Properties

## Standard

## Results

Water Absorption

ISO 10545-3

$E \leq 0.09\%$

Breaking Strength

ISO 10545-4

Complaint

MOH's Hardness

EN|0|

Chemical Resistance

(Acid & Bases)

ISO 10545-13

GLA

(Household Chemicals)

GA

Stain Resistance

ISO 10545-14

Class 5

## RELATED PRODUCTS

- 

### VEIN

\$0.00

- 

### GLACIER

\$0.00

- 

### STEAMSHIP

\$0.00