



TIVOLI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain	Non-Rectified	Matte	3/8"	14	7	Min. 1/8"
18x36 (Beige)	Porcelain	Rectified	Matte	3/8"	13.5	3	Min. 1/16"

TIVOLI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.05\%$
Breaking Strength	ISO 10545-4	$R \geq 35 \text{ N/mm}^2$
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Tivoli



TIVOLI

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige

Grigio

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

Color	Beige & Cream, White
Material	Stone
Finish	Matte
Price	\$\$

Tivoli quantity

Add to cart

SKU: tivoli

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

TIVOLI AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	Porcelain Non-Rectified	Matte	3/8"	14	7	Min. 1/8"	
18x36 (Beige)	Porcelain Rectified	Matte	3/8"	13.5	3	Min. 1/16"	

TIVOLI TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	$E \leq 0.05\%$
Breaking Strength	ISO 10545-4	$R \geq 35 \text{ N/mm}^2$
MOH's Hardness	EN 0	MOHS 6
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GLA GA
Stain Resistance	ISO 10545-14	Class 5

RELATED PRODUCTS



CREFOR

\$0.00



CARBONITE

\$0.00



BERSE

\$0.00