



TIVOLI AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|---------------|-----------|---------------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain | Non-Rectified | Matte | 3/8" | 14 | 7 | Min. 1/8" |
| 18x36 (Beige) | Porcelain | Rectified | Matte | 3/8" | 13.5 | 3 | Min. 1/16" |

TIVOLI TILE PERFORMANCE DATA

| Physical Properties | Standard | Results |
|--|-----------------|----------------------------|
| Dynamic Coefficient of Friction | D.C.O.F. > 0.42 | Meets or Exceeds Standard |
| Water Absorption | ISO 10545-3 | $E \leq 0.05\%$ |
| Breaking Strength | ISO 10545-4 | $R \geq 35 \text{ N/mm}^2$ |
| MOH's Hardness | EN 0 | MOHS 6 |
| Chemical Resistance (Acid & Bases) (Household Chemicals) | ISO 10545-13 | GLA GA |
| Stain Resistance | ISO 10545-14 | Class 5 |



PRODUCT DESCRIPTION

[Home](#) / [Porcelain & Ceramic Tile](#) / Tivoli



TIVOLI

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige

Grigio

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

RECOMMENDED INSTALLATIONS

Floor
Wall
Exterior

SHARE THIS STYLE



[GENERATE PDF](#)

ADDITIONAL INFORMATION

| | |
|----------|--|
| Color | Beige & Cream, White |
| Material | Stone |
| Finish | Matte |
| Price | \$\$ |

Tivoli quantity

Add to cart

SKU: tivoli

Categories: [Porcelain & Ceramic Tile](#), [Trade Professionals](#)

TIVOLI AVAILABLE SIZES

| Sizes | Type | Style | Finish | Thickness | Sqft/Carton | Pieces/Box | Recommended Grout Joint |
|---------------|-------------------------|-------|--------|-----------|-------------|------------|-------------------------|
| 12x24 | Porcelain Non-Rectified | Matte | 3/8" | 14 | 7 | Min. 1/8" | |
| 18x36 (Beige) | Porcelain Rectified | Matte | 3/8" | 13.5 | 3 | Min. 1/16" | |

TIVOLI TILE PERFORMANCE DATA

| Physical Properties | Standard | Results |
|--|-----------------|----------------------------|
| Dynamic Coefficient of Friction | D.C.O.F. > 0.42 | Meets or Exceeds Standard |
| Water Absorption | ISO 10545-3 | $E \leq 0.05\%$ |
| Breaking Strength | ISO 10545-4 | $R \geq 35 \text{ N/mm}^2$ |
| MOH's Hardness | EN 0 | MOHS 6 |
| Chemical Resistance (Acid & Bases) (Household Chemicals) | ISO 10545-13 | GLA GA |
| Stain Resistance | ISO 10545-14 | Class 5 |

RELATED PRODUCTS



COLORADO

\$0.00



MANDALAY

\$0.00



CEMENTONIA

\$0.00