TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

PRODUCT DESCRIPTION

TULLE

$0.00

- Description
- Additional information

STOCKED IN LINCOLN, NE

AVAILABLE COLORS

Beige
Taupe

Please contact the office for availability. 402-475-1300

RECOMMENDED INSTALLATIONS

Floor
Wall

SHARE THIS STYLE

GENERATE PDF

ADDITIONAL INFORMATION

Color	Beige & Cream, Taupe
Material	3D Wall, Fabric
Finish	Matte
Price	$

Tulle quantity
1

Add to cart

SKU: tulle

Categories: Ceramic Tile, Trade Professionals

TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN|0|	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

RELATED PRODUCTS

- ### CARBONITE

  $0.00

- ### COLORADO

  $0.00

- ### SARK STEEL

  $0.00