



## TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

## TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN 0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies



## PRODUCT DESCRIPTION

[Home](#) / [Trade Professionals](#) / Tulle



## TULLE

\$0.00

- [Description](#)
- [Additional information](#)

STOCKED IN LINCOLN, NE

#### AVAILABLE COLORS

Beige  
Taupe

Please contact the office for availability. [402-475-1300](tel:402-475-1300)

#### RECOMMENDED INSTALLATIONS

Floor  
Wall

#### SHARE THIS STYLE



[GENERATE PDF](#)

## ADDITIONAL INFORMATION

<b>Color</b>	<a href="#">Beige &amp; Cream, Taupe</a>
<b>Material</b>	<a href="#">3D Wall, Fabric</a>
<b>Finish</b>	<a href="#">Matte</a>
<b>Price</b>	<a href="#">\$</a>

Tulle quantity

Add to cart

SKU: tulle

Categories: [Ceramic Tile](#), [Trade Professionals](#)

## TULLE AVAILABLE SIZES

Sizes	Type	Style	Finish	Thickness	Sqft/Carton	Pieces/Box	Recommended Grout Joint
12x24	White Body	Rectified	Matte	3/8"	12	6	Min. 1/16"

## TULLE TILE PERFORMANCE DATA

Physical Properties	Standard	Results
Dynamic Coefficient of Friction	D.C.O.F. > 0.42	Meets or Exceeds Standard
Water Absorption	ISO 10545-3	E > 10%
Breaking Strength	ISO 10545-4	> 600 N
MOH's Hardness	EN   0	
Chemical Resistance (Acid & Bases) (Household Chemicals)	ISO 10545-13	GHB GLB
Stain Resistance	ISO 10545-14	Complies

## RELATED PRODUCTS



**SILK**

\$0.00



**CARBONITE**

\$0.00



**CEMENTONIA**

\$0.00